



370Z System Instructions

370Z Dual Nozzle Installation Guide

Part # 00-10007

INSTALLATION INSTRUCTIONS

INTRODUCTION

Thank you for purchasing the highest quality nitrous system on the market. Nitrous Outlet strives to offer the best product with the best price and customer service available. Nitrous Outlet has trained professionals on staff to help with any technical questions you may have before and after your installation. You can contact Nitrous Outlet at 1-866-648-7637 or sales@nitrousoutlet.com. All Nitrous Outlet systems are carefully designed to work on specific applications. We suggest contacting the tech department to learn what modifications, if any, are needed for this kit to work properly on your application. It is the purchaser's responsibility to follow all installation instruction guidelines and safety procedures supplied with the product. It is up to the customer to determine the compatibility of the product with the application the purchaser intends to install the product on. Nitrous Outlet assumes no responsibility or liability for damages incurred by these products manufactured or sold by Nitrous Outlet. Nitrous Outlet neither recommends nor condones the use of products manufactured or sold by Nitrous Outlet on vehicles, which may be driven on public roads or highways, and assumes no responsibility for damages incurred by such use. Nitrous Outlet accepts no responsibilities of knowing your state laws, and recommends that all products should be used for off road use only. These instructions will guide you through the installation of your Nitrous Outlet nitrous system. For the best results please follow the directions in order and step by step. This way you can insure you have a safe and properly installed system. Use red loc-tite on all pipe thread connections. Do NOT use any type of sealer on the AN fittings (Flare, hose, and bottle connections) AN Fittings are designed to use the tapered seat to seal. NEVER USE TEFLON TAPE OR PASTE. If you use loc-tite you will need to heat the connector to loosen. Before starting your installation, disconnect the negative battery cable. See your owner's manual for information if needed.



370Z System Instructions

370Z Dual Nozzle Installation Guide

Part # 00-10007

INSTALLATION INSTRUCTIONS

Bottle placement is critical to the performance of your Nitrous Outlet Nitrous system. It is important to mount your nitrous bottle properly in order to ensure that the siphon tube located in the nitrous bottle picks up liquid nitrous.

If mounting the bottle in lay-down position, the bottle valve must be towards the front of the vehicle with the label facing up.

If mounting the bottle vertically, the valve handle and label must face toward the front of the vehicle. This position will orientate the siphon tube at the back of the bottle where the liquid nitrous will be during acceleration.

If mounting the bottle sideways in the vehicle the valve handle and label must be angled around 45* toward the front of the vehicle. This position will orientate the siphon tube at the back of the bottle where the liquid nitrous will be during acceleration.

1. Insert the bottle nipple into the bottle nut and tighten on to the bottle valve. Fasten bottle orientation.

2. Place the bottle, still in the brackets, in a mounting location that will provide easy access. Using the brackets as a pattern, mark and drill four 3/8" holes.

NOTE: Before drilling check for fuel tank, lines, wiring, etc. Secure bracket using the four supplied 5'16 bolts.



WWW.NITROUSOUTLET.COM

IMPORTANT—All appropriate safety equipment (e.i., gloves, tools) must be used during the installation of this product(s). Nitro Dave's LLC accepts no responsibility for injuries resulting in the installation of any product(s).



370Z System Instructions

370Z Dual Nozzle Installation Guide

Part # 00-10007


INSTALLATION INSTRUCTIONS

NOZZLE INSTALLATION

The location of the nozzle will determine the solenoid placement. This system comes with 2-foot lines to run from the solenoid to the nozzle. On a wet single nozzle system the recommended nozzle location will be mounted into the inlet tube 2-6" in front of the throttle body. On a single nozzle dry system the nozzle will be placed in the air box before the mass air meter. Certain application will dictate other nozzle location. Please call technical support if you need additional assistance at 1-866-648-7637.

1. Determine the nozzle locations. This area should be as flat as possible and free from obstruction. Mark and drill a 9/16" hole in the inlet tube.
2. Using a silicone RTV type sealant, apply a thin bead around the nozzle adapter surface. Insert adapter from the inside of the inlet tube and snug the locking lug from the outside.
3. Thread the nozzles into the adapters and position so that the discharge is pointed towards the throttle bodies.
3. Using the supplied jet card choose the lowest horsepower jets available. Place jets into nozzle. It is always best to start small and work your way up to larger jets. Attach the black stainless line to the nozzle fitting marked "N2O" and the red line to the side marked "fuel"

NOTE: Always check the jets for obstruction before using.





370Z System Instructions

370Z Dual Nozzle Installation Guide

Part # 00-10007

INSTALLATION INSTRUCTIONS

ROUTING THE NITROUS FEED LINE

NOTE: Place a piece of tape over the end of the line before routing to prevent debris from entering the line.

The 16' -4 AN nitrous feed line may be routed to the engine either through the passenger compartment or underneath the vehicle.

If routing the main feed line under the vehicle route the line as to avoid kinks, possible abrasion points or exhaust components. Drill a $\frac{3}{4}$ " hole in a suitable area near the bottle valve. Starting at the bottle (do not attach line to nipple) route the line to the engine bay. Following the factory fuel lines is usually the best route. Make sure to keep a safe distance from any moving parts, suspension components, and hot engine parts. Make sure to secure the line where possible. Avoid any electrical connections as sparks can destroy the lining and cause a nitrous leak. If routing the main feed line inside of the vehicle, route the main feed line from the back of the vehicle to the front exiting through the firewall into the engine bay, avoiding kinks, possible abrasion points, or electrical components.

INSTALL THE FUEL RAIL ADAPTER

The Billet 350 Z fuel rail adapter installs between the stock fuel rail adapter and the stock fuel pressure regulator. Take the gas cap off to relieve pressure from the fuel system and simply unbolt the fuel pressure regulator and place the adapter in between the fuel rail and regulator with the -4 fitting facing the direction of where your solenoid will be mounted. Longer bolts are provided for installation



WWW.NITROUSOUTLET.COM

IMPORTANT—All appropriate safety equipment (e.i., gloves, tools) must be used during the installation of this product(s). Nitro Dave's LLC accepts no responsibility for injuries resulting in the installation of any product(s).



370Z System Instructions

370Z Dual Nozzle Installation Guide

Part # 00-10007

INSTALLATION INSTRUCTIONS

SOLENOID MOUNTING

1. Nitrous Outlet nitrous solenoids are designed with ¼ NPT inlets and two 1/8 NPT discharge ports. The side discharge is for a purge and the bottom location is the main nitrous discharge port. If you are not using a purge there is an included 1/8 plug to block off the purge port. Install all solenoid fitting using red loc-tite. **DO NOT USE TEFLON TAPE.** The 1/4x-4 fitting will go in the nitrous solenoid inlet. The 1/8x-3x-3 T Fitting will go in the bottom discharge. The 1/8x-4 will go in the fuel solenoid inlet, and the 1/8x-3x3 T will go in the fuel side discharge port.
2. The solenoid mounting brackets are designed to be universal. Start by mounting the bracket to the solenoids. Do not tighten, as you may have to flip the bracket over to align the solenoid for proper orientation. Try to locate an existing screw or bolt to mount the brackets. Remember you will need to locate the solenoids within reach of the nozzle lines. Tighten all mounting screws.

NOTE: The solenoids can be mounted vertically, horizontally or upside down.

Thread the black -3 line onto the nitrous discharge and the red -3 line to the fuel discharge port. The nitrous main feed line will attach to the nitrous solenoid inlet. The fuel supply will come from the provided fuel rail adapter.

NOTE: Before attaching remove the tape and purge the feed line to remove any debris from the line. You can do this by blowing compressed air into the line while having an assistant hold the other end away from the car and any bystanders. Immediately after purging attach the feed line to the nitrous solenoid and the bottle nipple.

